



AUTOX GEAR OIL SHOT 80W-90 is a premium scooter gear oil that meets the API GL-5 standard for scooter final gearboxes.

PERFORMANCES

SAE 80W-90;
API GL-5;
ZF TE-ML 07A/08/24A

APPLICATIONS

GEAR OIL SHOT 80W-90 lubricates the scooter's final gearbox. SAE 80W-90 viscosity grade is ideal for all scooters.

ADVANTAGES

- High load carrying capacity ensures that the gearbox operates at high speeds and extends component life.
- Reduce the volume of the high-speed ride.
- Protection from Extreme Pressure (Anti-EP).
- Excellent anti-wear, anti-corrosion, and anti-rust properties.

CAPACITY

120 ML

CHARACTERISTICS

PROPERTIES	METHODS	VALUES	UNITS
Appearance	Visual	Amber clear liquid	
Density at 20°C	ASTM D4052	0.8715	g/cm ³
Kinematic Viscosity at 40°C	ASTM D445	135.05	cSt
Kinematic Viscosity at 100°C	ASTM D445	15.67	cSt
Viscosity Index	ASTM D2270	121	
Flash point by COC	ASTM D92	250	°C

These properties are typical of current production. Whilst future production will conform to AutoX's specification, variations in these properties may occur.