



**CAPACITY**

800ML

**PERFORMANCES**

SAE 10W-40; API SN; JASO MB

**FAST SCOOT** is a high - performance **4-Stroke Scooter** engine oil formulated with **Synthetic Clean+ Technology** to offer high engine temperature protection as well as reduce harmful exhaust emissions.

The unique formulation allows for **FAST SCOOT** smooth acceleration with lower harmful exhaust emission providing a smooth riding experience wherever you ride.

Our passion for pure riding and clean air is the reason why **FAST SCOOT** is a transparent **Blue SAPPHIRE** color to protect against negative engine energies and provide cleaner air.

**ADVANTAGES**

- Suitable for use on city roads in continuous start-stop mode.
- Excellent anti-wear, anti-corrosion, and anti-rust properties.
- Excellent thermal and oxidation stability.

**APPLICATIONS**

- **FAST SCOOT** is recommended for four-stroke engine scooters with CVT transmission technology that operate high temperatures and speeds.
- It is completely appropriate for all scooter manufacturers from Japan, Europe, and North American.

**CHARACTERISTICS**

PROPERTIES	METHODS	VALUES	UNITS
Appearance	Visual	Blue clear liquid	
Density at 15°C	ASTM D4052	0.8584	g/cm3
Kinematic Viscosity at 40°C	ASTM D445	94.59	cSt
Kinematic Viscosity at 100°C	ASTM D445	14.52	cSt
Viscosity Index	ASTM D2270	159	
Flash point by COC	ASTM D92	236	°C
Pour point	ASTM D5950	-42	°C
Total base number	ASTM D2896	7.5	mgKOH/g
CCS at -25°C	ASTM D5293	4081	mPa.s

*These properties are typical of current production. Whilst future production will conform to AutoX's specification, variations in these properties may occur.*