



CAPACITY

0.8L/1L

PERFORMANCES

SAE 10W-40; API SN; JASO MA/MA2

FAST is a high - performance **4-Stroke** engine oil formulated with **Synthetic Clean+ Technology** to offer high engine temperature protection as well as reduce harmful exhaust emissions.

The unique formulation allows for **FAST** smooth acceleration with lower harmful exhaust emission providing a smooth riding experience wherever you ride.

Our passion for pure riding and clean air is the reason why **FAST** is a transparent **Blue SAPPHIRE** color to protect against negative engine energies and provide cleaner air.

ADVANTAGES

- Exceptional acceleration and smooth gear changes.
- Suitable for use on city roads in continuous start-stop mode.
- Excellent anti-wear, anti-corrosion, and anti-rust properties.
- Excellent thermal and oxidation stability.

APPLICATIONS

- **FAST** is recommended for four-stroke engine motorcycles that operate at high temperatures and speeds (with wet clutch).
- It is completely compatible with all motorcycle brands from Japan, Europe, and North America.
EX: Honda, Yamaha,...

CHARACTERISTICS

PROPERTIES	METHODS	VALUES	UNITS
Appearance	Visual	Blue clear liquid	
Density at 15°C	ASTM D4052	0.8577	g/cm ³
Kinematic Viscosity at 40°C	ASTM D445	91.8	cSt
Kinematic Viscosity at 100°C	ASTM D445	14.08	cSt
Viscosity Index	ASTM D2270	158	
Flash point by COC	ASTM D92	228	°C
Pour point	ASTM D5950	-45	°C
Total base number	ASTM D2896	6.8	mgKOH/g
CCS at -25°C	ASTM D5293	3863	mPa.s

These properties are typical of current production. Whilst future production will conform to AutoX's specification, variations in these properties may occur.